



## MATERIAL SAFETY DATA SHEET

### **1. PRODUCT AND COMPANY IDENTIFICATION**

**Manufacturer:**

**Radco Industries, Inc.**, PO Box 305 LaFox, IL 60147 USA  
Emergency Phone: (630) 232-7966

Website: www.Xceltherm.com

Product Name: **XCEL THERM® HT** Heat Transfer Fluid  
Effective Date: 08/26/09

**Emergency Phone Numbers:**

For chemical emergency, spill, leak, fire exposure, accident or medical emergency, call CHEMTREC:  
North America 1-800-424-9300  
International +1 703-527-3887

For shipping emergency or off-hours rush orders call:  
1-630-232-7966 or 1-630-336-6728

### **2. COMPOSITION / INFORMATION ON INGREDIENTS**

COMPONENT	CAS#	CONCENTRATION
Blend of Substituted Aromatic Hydrocarbons	29589-57-9	100.0 %

Note(s): Not a Hazardous Material for DOT shipping

### **3. HAZARD IDENTIFICATION**

#### **POTENTIAL HEALTH EFFECTS**

**Ingestion:**

Single dose oral toxicity is low. If aspirated, may cause lung damage due to chemical pneumonia, a condition caused by petroleum and petroleum-like solvents.

**Skin Absorption:**

A single prolonged exposure is not likely to result in the material being absorbed through the skin in harmful amounts.

**Inhalation:**

In general, overexposure to high atmospheric concentrations of alkyl-substituted aromatics may produce central nervous depression, headache, dizziness, nausea and loss of appetite.

**Eye contact:**

May cause transient eye irritation (tears, blurred vision, and redness).

### **4. FIRST AID MEASURES**

**Ingestion:**

DO NOT induce vomiting. Seek medical attention immediately.

**Skin Absorption:**

Wash skin with soap and water. Remove contaminated clothing. Wash clothing before re-use. Obtain medical attention if irritation persists.

**Inhalation:**

Obtain medical attention. Oxygen may be given by qualified personnel if breathing is difficult or cyanosis (blue discoloration of skin) is noted. Give artificial respiration if not breathing. Remove to fresh air if aerosol spray is inhaled. Aspiration may cause pulmonary edema or aspiration pneumonia. Exposed persons should be kept under medical observation for at least 48 hours because delayed effects may occur.

**Eye contact:**

Flush eyes thoroughly with water for several minutes. Obtain medical attention if discomfort persists.

**XCEL THERM® HT/MSDS**  
**RADCO INDUSTRIES, INC.**  
 P.O. Box 305  
 LaFox IL 60147

---

## 5. FIRE-FIGHTING MEASURES

---

<b>Flash point :</b>	> 160 °C (> 320°F)	<b>Autoignition Temperature :</b>	> 450 °C (> 842°F)
----------------------	--------------------	-----------------------------------	--------------------

### NFPA CLASSIFICATION

Health: 1	Flammability: 1	Reactivity: 0	Special provisions: none
-----------	-----------------	---------------	--------------------------

#### Special fire fighting procedures

Use water spray to cool fire-exposed containers and structures. If a rail or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

#### Special protective equipment for firefighters

Body covering protective clothing, full "turn-out" gear. Self-contained breathing apparatus with full face-piece operated in positive pressure mode.

#### Extinguishing media

Suitable: Treat as an oil fire.  
 Small fires:  
 - CO2  
 - dry powder  
 - foam  
 Large fires:  
 - alcohol-type foam or universal-type foams  
 - water fog

Unsuitable: Oil will float on water and can spread any fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

#### Personal precautions

Wear protective clothing when taking up spill. Eliminate sources of ignition.

#### Environmental precautions

This product is insoluble in water and will float on the surface. Prevent from entering sewers or drains. Should this product enter sewers or drains, it should be pumped out into an open vessel. Emergency services may need to be called to assist in this operation.

#### Methods for cleaning up

Floor may be slippery; use care to avoid falling.

Small spills Absorb on inert material such as sand, earth, vermiculite.

---

## 7. HANDLING AND STORAGE

---

### HANDLING

#### Handling precautions

Never use pressure to empty drums. Keep drums tightly closed to prevent contamination. Residual vapors may explode on ignition; do not puncture, drill, grind, or weld near this container. Electrically bond and ground all containers and equipment before transfer or use of material.

### STORAGE

#### Storage requirements

Normal precautions common to safe manufacturing practice should be followed in handling and storage. Store in a dry location. Keep out of strong sunlight. Keep away from heat and flame. Keep container tightly closed.

#### Further information on storage

Keep away from strong oxidizing agents.

XCEL THERM® HT/MSDS  
 RADCO INDUSTRIES, INC.  
 P.O. Box 305  
 LaFox IL 60147

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### PERSONAL PROTECTION

#### Respiratory protection

If vapor and/or mist is generated by heating, spraying, etc., wear an organic vapor respirator with a mist filter. No special respiratory protection is normally required.

#### Hand protection / protective gloves

Wear oil resistant gloves.

#### Eye protection

Face shield or chemical splash goggles in case of splashing.

#### Skin protection

Wear protective clothing, such as long sleeves to minimize skin contact.

#### Industrial hygiene measures

Remove contaminated clothing and clean it.

Do not eat or drink at work.

### ENGINEERING CONTROLS

#### Ventilation

Local ventilation is needed in the presence of airborne mists.

### EXPOSURE LIMITS

<u>Component</u>	<u>Type</u>	<u>Value</u>	<u>Remark</u>
Product Oil Mist	TWA (mist), ACGIH	None Established	NONE
	STEL (mist), ACGIH	None Established	

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

<b>Physical state</b>	Liquid
<b>Color</b>	Water-white to straw yellow
<b>Odor</b>	None

### OTHER PROPERTIES

<b>Boiling point</b>	290 °C at STP (min).
<b>Specific gravity (H<sub>2</sub>O=1)</b>	1.00 (Water = 1.00)
<b>Vapor pressure</b>	0.001 mmHg at 20 °C
<b>Solubility in water</b>	< 5 ppm
<b>Solubility in organic solvents</b>	Soluble
<b>Vapor Density</b>	8.3 (Air= 1.00)
<b>Flash point</b>	>160 °C (320 °F) Method: Cleveland open cup ASTM D 92
<b>Percent volatiles</b>	Nil
<b>Kinematic viscosity</b>	Not Determined

---

## 10. STABILITY AND REACTIVITY

---

**Stability:** Stable.

**Incompatible materials**

Normally unreactive; however avoid contact with:  
Strong oxidizing agents.

**Hazardous combustion products**

Burning can produce the following combustion products:  
Oxides of carbon, Soot.

**Hazardous polymerization:** Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

### SWALLOWING

**Acute effects**

See Hazard Identification and First Aid sections of this MSDS.

**Test results**

Acute toxicity: LD50 - Rat  
Result: > 2 g/kg  
Remark: Test results are based on analogy with a similar material.

### SKIN ABSORPTION

**Acute effects**

Harmful effects are not expected from short periods of contact.

**Effects of repeated overexposure**

Prolonged or repeated contact may lead to skin irritation by dermatitis or oil acne.

### INHALATION

**Acute effects**

Inhalation of mist or spray may be harmful.

**Chronic effects**

Aspiration may cause pulmonary edema or aspiration pneumonia.  
Deposits in the lung may lead to fibrosis and reduced pulmonary function.  
Prolonged or repeated inhalation of excessive amounts of oil mist or vapors may cause irritation of the respiratory tract.

### SKIN CONTACT

**Acute effects**

No evidence of permanent harmful effects from available information.

### EYE CONTACT

**Acute effects**

No evidence of permanent harmful effects from available information.

### SENSITIZATION

Test results: Species: Skin - Guinea pigs  
Result: Non sensitizing.

### CARCINOGENICITY

**Assessment**

No evidence of carcinogenic activity

---

## 12. ECOLOGICAL INFORMATION

---

This product is toxic for aquatic life.

## 13. DISPOSAL CONSIDERATIONS

**General:** Incineration is the best means of disposal. Dispose of in accordance with appropriate Federal, State, and local regulations. If discarded in its purchased form, this material would not be considered at this time as a hazardous waste either by listing or by characteristics under Federal Hazardous Waste Regulations, 40 C.F.R. 261. Consult state and local regulations for proper disposal.

---

## 14. TRANSPORT INFORMATION

---

### DOT Classification

This product is not regulated by DOT.

<b>Freight description road:</b>	MIXED AROMATICS, N.O.I.B.N
----------------------------------	----------------------------

### IMDG Classification

This product is not regulated by IMDG.

### ICAO Classification

This product is not regulated by ICAO.

---

## 15. REGULATORY INFORMATION

---

**EPA Hazard Categories (SARA 311, 312):** None

### CHEMICAL INVENTORY

United States: The ingredients of this product are listed on the TSCA inventory.

---

## 16. OTHER INFORMATION

---

### RECOMMENDED USES AND RESTRICTIONS

Please consult the product and/or application information bulletins for this product.

### HMIS RATING

Health: 1	Flammability: 1	Reactivity: 0	PPI: -
-----------	-----------------	---------------	--------

### LEGEND

STP	Standard temperature and pressure
W/W	Weight/Weight
0 (HMIS)	Minimal hazard
1 (HMIS)	Slight hazard
2 (HMIS)	Moderate hazard
3 (HMIS)	Serious hazard
4 (HMIS)	Severe hazard
X (HMIS)	Personal protection rating to be supplied by user depending on use conditions

WARNING: "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove and even a trace of remaining material constitutes as explosive hazard. "Empty" drums should be completely drained, properly bunged, and promptly returned to a drum recycler. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION STATED IS TO THE BEST OF RADCO'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE TO ITS ACCURACY, RELIABILITY, OR COMPLETENESS, AND RADCO DOES NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL SHOULD BE USED WITH CAUTION TO GUARD AGAINST UNKNOWN HAZARDS. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, RADCO DOES NOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

® Indicates a registered trademark of **Radco Industries, Inc.**