



RADCOLUBE® LTGO

Safety Data Sheet

MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature

Issue date: 9/12/2019

Revision date: 2/14/2024

Supersedes: 12/15/2023

Version: 5.0

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Trade name	RADCOLUBE® LTGO
Specification:	MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature
Qualification Number (Date):	AR 22-01 (1 February 2022)
Military Symbol:	LAW
NATO Code:	0-157
National Stock Number(s) (NSN):	9150-00-292-9689 (Quart) 9150-00-292-9687 (5 Gallon Pail)

1.2. Recommended use and restrictions on use

Use of the substance/mixture:	The lubricating oil covered by this specification is intended primarily for the lubrication of aircraft and ground weapons to ensure efficient firing at low temperatures. The oil covered by this specification is considered military unique because it must perform at temperatures between 0°F to -70°F (-17.8°C to -56.6°C).
-------------------------------	---

1.3. Supplier

Manufacturer

Radco Industries Inc.
CAGE Code 6ZS16
700 Kingsland Drive
Batavia, Illinois 60510
United States
T (630) 232-7966
www.radcoind.com

1.4. Emergency telephone number

Emergency number:	For Chemical Emergency Call CHEMTREC 24hr/day 7days/week Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)
-------------------	--

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US):



Signal word (GHS US):

Danger

Hazard statements (GHS US):

H304 - May be fatal if swallowed and enters airways

H332 - Harmful if inhaled

Precautionary statements (GHS US):

P261 - Avoid breathing vapors, mist.

P271 - Use only outdoors or in a well-ventilated area.

P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER, a doctor if you feel unwell.

P331 - Do NOT induce vomiting.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification:

None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Synthetic hydrocarbon* (Base Stock)	CAS-No.: Trade Secret	Trade Secret	Acute Tox. 4 (Inhalation:dust,mist), H332 Asp. Tox. 1, H304
Proprietary Additive 1* (Additive)	CAS-No.: Trade Secret	< 2	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Hydrocarbon solvent* (Solvent)	CAS-No.: Trade Secret	0.01 – 0.1	Flam. Liq. 3, H226 Asp. Tox. 1, H304

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general:

Call a physician immediately.

RADCOLUBE® LTGO

MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact: Wash skin with plenty of water.

First-aid measures after eye contact: Rinse eyes with water as a precaution.

First-aid measures after ingestion: Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact: None under normal conditions.

Symptoms/effects after eye contact: None under normal conditions.

Symptoms/effects after ingestion: Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard: No fire hazard.

Explosion hazard: No direct explosion hazard.

Hazardous decomposition products in case of fire: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment: Wear recommended personal protective equipment.

Emergency procedures: Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

RADCOLUBE® LTGO

MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up: Take up liquid spill into absorbent material.

Other information: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed: Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling: Wear personal protective equipment. Use only outdoors or in a well-ventilated area.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures: Keep in a cool, well-ventilated place away from heat.

Storage conditions: Store locked up.

Packaging materials: Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

RADCOLUBE® LTGO	
No additional information available	
Synthetic hydrocarbon	
No additional information available	
Proprietary Additive 1	
No additional information available	
Hydrocarbon solvent	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³ (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023

RADCOLUBE® LTGO

MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls: Ensure good ventilation of the work station.

Environmental exposure controls: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	Liquid.
Color:	Light yellow
Odor:	Characteristic odour
Odor threshold:	No data available
pH:	No data available
Melting point:	Not applicable
Freezing point:	≤ -69 °C (ASTM D97 Pour point)
Boiling point:	> 300 °C
Flash point:	164.4 °C
Relative evaporation rate (butyl acetate=1):	No data available

RADCOLUBE® LTGO**MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability:	Not applicable.
Vapor pressure:	< 0.4 mm Hg at 25°C (77°F)
Relative vapor density at 20°C:	No data available
Relative density:	0.824 at 15.6°C (60°F) (water = 1)
Density:	6.9 lb/gal at 15.6°C (60°F)
Solubility:	Insoluble in water.
Partition coefficient n-octanol/water (Log Pow):	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	6.1 mm ² /s at 40°C
Viscosity, dynamic:	No data available
Explosion limits:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available

9.2. Other information

VOC content:	0 %
--------------	-----

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral):	Not classified
Acute toxicity (dermal):	Not classified
Acute toxicity (inhalation):	Inhalation:dust,mist: Harmful if inhaled.
Skin corrosion/irritation:	Not classified
Carcinogenicity:	Not classified
Aspiration hazard:	May be fatal if swallowed and enters airways.
Viscosity, kinematic:	6.1 mm ² /s at 40°C
Symptoms/effects after inhalation:	Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact:	None under normal conditions.
Symptoms/effects after eye contact:	None under normal conditions.
Symptoms/effects after ingestion:	Risk of lung edema.
STOT-single exposure:	Not classified
STOT-repeated exposure:	Not classified
Reproductive toxicity:	Not classified

RADCOLUBE® LTGO

ATE US (dust, mist):	1.671 mg/l/4h
----------------------	---------------

Synthetic hydrocarbon

LD50 oral rat:	> 5000 mg/kg
LD50 dermal rabbit:	> 3000 mg/kg
LC50 Inhalation - Rat:	1.17 mg/l
ATE US (vapors):	1.17 mg/l/4h
ATE US (dust, mist):	1.17 mg/l/4h

Proprietary Additive 1

LD50 oral rat:	> 2500 mg/kg
LD50 dermal rabbit:	10000 mg/kg
LC50 Inhalation - Rat:	9000 mg/l (1 Hour)
ATE US (dermal):	10000 mg/kg body weight
ATE US (vapors):	9000 mg/l/4h
ATE US (dust, mist):	9000 mg/l/4h

Hydrocarbon solvent

LD50 oral rat:	> 5000 mg/kg body weight (OECD 420 method)
LD50 dermal rabbit:	> 2000 mg/kg body weight (OECD 402 method)

RADCOLUBE® LTGO**MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LC50 Inhalation - Rat:	> 5.28 mg/l/4h (OECD 403 method)
Synthetic hydrocarbon	
Serious eye damage/irritation:	Not classified
Proprietary Additive 1	
Corrosivity	Negative
Skin corrosion/irritation	Irritating to skin
Serious eye damage/irritation:	Not classified
Hydrocarbon solvent	
Serious eye damage/irritation:	Not classified
Synthetic hydrocarbon	
Respiratory or skin sensitization:	Not classified
Proprietary Additive 1	
Serious eye damage/irritation	Irritating
Respiratory or skin sensitization:	Not classified
Hydrocarbon solvent	
Respiratory or skin sensitization:	Not classified
Synthetic hydrocarbon	
Germ cell mutagenicity:	Not classified
Proprietary Additive 1	
Germ cell mutagenicity:	Not classified
Hydrocarbon solvent	
Germ cell mutagenicity:	Not classified
Hydrocarbon solvent	
NOAEL (animal/male, F0/P):	≥ 3000 mg/kg body weight
Hydrocarbon solvent	
NOAEL (oral,rat,90 days):	750 mg/kg body weight female)
NOAEC (inhalation,rat,vapor,90 days):	≥ 0.024 mg/l Air (OECD 412 method)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Proprietary Additive 1	
EC50 - Crustacea [1]:	≥ 0.18 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]:	> 0.27 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation: Disposal must be done according to official regulations.
 Waste treatment methods: Dispose of contents/container in accordance with licensed collector's sorting instructions.
 Sewage disposal recommendations: Disposal must be done according to official regulations.
 Product/Packaging disposal recommendations: Disposal must be done according to official regulations.
 Additional information: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA / ICAO / ADN / RID / ADG

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT): Not applicable
 Proper Shipping Name (TDG): Not applicable
 Proper Shipping Name (IMDG): Not applicable
 Proper Shipping Name (IATA): Not applicable

RADCOLUBE® LTGO

MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT): Not applicable

TDG

Transport hazard class(es) (TDG): Not applicable

IMDG

Transport hazard class(es) (IMDG): Not applicable

IATA

Transport hazard class(es) (IATA): Not applicable

14.4. Packing group

Packing group (DOT): Not applicable

Packing group (TDG): Not applicable

Packing group (IMDG): Not applicable

Packing group (IATA): Not applicable

14.5. Environmental hazards

Other information: No supplementary information available.

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

RADCOLUBE® LTGO**MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	CAS-No.	Listing	Commercial status	Flags
Synthetic hydrocarbon		Present	Active	PMN
Proprietary Additive 1		Not present	-	
Hydrocarbon solvent		Present	Active	

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations**CANADA****Synthetic hydrocarbon**

Listed on the Canadian NDSL (Non-Domestic Substances List)

Hydrocarbon solvent

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations**Hydrocarbon solvent**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/14/2024


Full text of H-phrases	
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

RADCOLUBE® LTGO

MIL-PRF-14107D Lubricating Oil, Weapons, Low Temperature

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.	
NFPA fire hazard	1 - Materials that must be preheated before ignition can occur.	
NFPA reactivity	0 - Material that in themselves are normally stable, even under fire conditions.	

Hazard Rating	
Health	2 Moderate Hazard - Temporary or minor injury may occur
Flammability	1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular process or for any particular purpose. Such information stated is to the best of Radco's knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made to its accuracy, reliability, or completeness, purchasers, users and distributors are not relying on any promise, representation, or recommendation made by Radco, and Radco does not accept liability for any loss or damage that may occur from the use of this information. Final determination of suitability of any material is the sole responsibility of the user. All material should be used with caution to guard against unknown hazards. Although certain hazards are described herein, Radco does not guarantee that these are the only hazards that exist.