



# RADCOLUBE® RHP6083

## Safety Data Sheet

### MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation

Issue date: 4/14/2025

Revision date: 8/15/2025

Supersedes: 8/8/2025

Version: 3.0

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

## SECTION 1: Identification

### 1.1. Identification

Trade name	RADCOLUBE® RHP6083
Radco Product Code:	RHP6083 (23271-G)
Specification:	MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation
Qualification Number (Date):	H-6068 (25 August 2020) H-6072 (28 September 2023) H-6074 (2 May 2025)
Military Symbol:	OHT
NATO Code:	C-635
National Stock Number(s) (NSN):	9150-00-935-9807 (Quart) 9150-00-935-9808 (Gallon) 9150-00-935-9809 (5 Gallon Pail) 9150-00-935-9810 (55 Gallon Drum)

### 1.2. Recommended use and restrictions on use

Use of the substance/mixture:	This product meets the requirements for one grade of petroleum base hydraulic fluid for use in the -54°C to +135°C (-65.2°F to 275°F) temperature range. This fluid is rust inhibited and used both as a preservative for hydraulic systems and components as well as being an operational fluid. This hydraulic fluid will not be used for aircraft systems, aircraft ground support equipment, or the preservation of aircraft components.
-------------------------------	--

### 1.3. Supplier

#### Manufacturer

Radco Industries L.L.C.  
CAGE Code 6ZS16  
700 Kingsland Drive  
Batavia, Illinois 60510  
United States  
T (630) 232-7966  
[www.radcoind.com](http://www.radcoind.com)

#### Manufacturer

Radco Industries L.L.C.  
CAGE Code 1RVC4  
39W930 Midan Drive  
LaFox, Illinois 60147  
United States  
T (630) 232-7966  
[www.radcoind.com](http://www.radcoind.com)

### 1.4. Emergency telephone number

Emergency number:	For Chemical Emergency Call CHEMTREC 24hr/day 7days/week Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)
-------------------	--

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

# RADCOLUBE® RHP6083

## MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation

### Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

#### GHS US classification

Reproductive toxicity, Category 2	H361	Suspected of damaging fertility.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (liver) through prolonged or repeated exposure (oral).
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.
Full text of H statements : see section 16		

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US):



Signal word (GHS US):

Danger

Hazard statements (GHS US):

H304 - May be fatal if swallowed and enters airways  
H361 - Suspected of damaging fertility.  
H373 - May cause damage to organs (liver) through prolonged or repeated exposure (oral)  
Precautionary statements (GHS US):  
P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P260 - Do not breathe fume, spray, vapors, mist.  
P280 - Wear protective gloves, eye protection, protective clothing.  
P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P331 - Do NOT induce vomiting.  
P405 - Store locked up.  
P501 - Dispose of contents and container to an approved waste disposal plant.

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	CAS-No.	%	GHS US classification
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	10 – 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated middle	64742-46-7	10 – 50	Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Synthetic Hydrocarbon*	Trade Secret	5 – 10	Asp. Tox. 1, H304
Mixture of aminic antioxidants, phenolic antioxidants	68411-46-1	0.5 – 5	Repr. 2, H361 STOT RE 2, H373
Napthalenesulfonic acid, dinonyl-, barium salt (2:1)	25619-56-1	< 5	Aquatic Chronic 2, H411

# RADCOLUBE® RHP6083

## MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation

### Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Name	CAS-No.	%	GHS US classification
Distillates (petroleum), hydrotreated light	64742-47-8	0.01 – 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general:	Call a physician immediately.
First-aid measures after inhalation:	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact:	Wash skin with plenty of water.
First-aid measures after eye contact:	Rinse eyes with water as a precaution.
First-aid measures after ingestion:	Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation:	Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact:	None under normal conditions.
Symptoms/effects after eye contact:	None under normal conditions.
Symptoms/effects after ingestion:	Risk of lung edema.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media:	Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard:	No fire hazard.
Explosion hazard:	No direct explosion hazard.
Hazardous decomposition products in case of fire:	Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions:	Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

---

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

General measures: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.  
Absorb spillage to prevent material-damage.

**6.1.1. For non-emergency personnel**

Protective equipment: Wear recommended personal protective equipment.

Emergency procedures: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray.

**6.1.2. For emergency responders**

Protective equipment: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

For containment: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information: Dispose of materials or solid residues at an authorized site.

**6.4. Reference to other sections**

For further information refer to section 13.

---

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Additional hazards when processed: Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

**7.2. Conditions for safe storage, including any incompatibilities**

Technical measures: Keep in a cool, well-ventilated place away from heat.

Storage conditions: Store locked up.

Packaging materials: Store always product in container of same material as original container.

---

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

**RADCOLUBE® RHP6083****MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation**

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>RADCOLUBE® RHP6083</b>	
No additional information available	
<b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b>	
No additional information available	
<b>Synthetic Hydrocarbon</b>	
No additional information available	
<b>Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)</b>	
No additional information available	
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Barium, soluble compounds (as Ba)
OSHA PEL TWA	0.5 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)</b>	
No additional information available	
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
No additional information available	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2025
<b>Distillates (petroleum), hydrotreated middle (64742-46-7)</b>	
No additional information available	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (I - Inhalable particulate matter)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Petroleum distillates (Naphtha)(Rubber Solvent)
OSHA PEL TWA	2000 mg/m <sup>3</sup>

## RADCOLUBE® RHP6083

### MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation

#### Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

## 8.2. Appropriate engineering controls

Appropriate engineering controls: Ensure good ventilation of the work station.  
Environmental exposure controls: Avoid release to the environment.

## 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Wear recommended personal protective equipment.

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
[In case of inadequate ventilation] wear respiratory protection.

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	Clear liquid.
Color:	red
Odor:	Petroleum-like odor
Odor threshold:	No data available
pH:	No data available
Melting point:	Not applicable
Freezing point:	≤ -63 °C (ASTM D97 Pour point)
Boiling point:	≥ 200 °C

## **RADCOLUBE® RHP6083**

### **MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation**

#### Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Flash point:	84 – 94 °C (ASTM D93 Flash point)
Relative evaporation rate (butyl acetate=1):	No data available
Flammability:	Not applicable.
Vapor pressure:	No data available
Relative vapor density at 20°C:	No data available
Relative density:	No data available
Density:	0.866 – 0.8874 at 15.6°C (Water = 1)
Solubility:	Insoluble in water.
Partition coefficient n-octanol/water (Log Pow):	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	13.2 – 17.3 mm <sup>2</sup> /s at 40°C (104°F)
Viscosity, dynamic:	No data available
Explosion limits:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available

## **9.2. Other information**

No additional information available

---

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

The product is non-reactive under normal conditions of use, storage and transport.

### **10.2. Chemical stability**

Stable under normal conditions.

### **10.3. Possibility of hazardous reactions**

No dangerous reactions known under normal conditions of use.

### **10.4. Conditions to avoid**

None under recommended storage and handling conditions (see section 7).

### **10.5. Incompatible materials**

No additional information available

### **10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects**

Acute toxicity (oral):	Not classified
Acute toxicity (dermal):	Not classified
Acute toxicity (inhalation):	Not classified
Skin corrosion/irritation:	Not classified
Carcinogenicity:	Not classified
Aspiration hazard:	May be fatal if swallowed and enters airways.
Viscosity, kinematic:	13.2 – 17.3 mm <sup>2</sup> /s at 40°C (104°F)
Symptoms/effects after inhalation:	Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact:	None under normal conditions.
Symptoms/effects after eye contact:	None under normal conditions.
Symptoms/effects after ingestion:	Risk of lung edema.
STOT-single exposure:	Not classified
STOT-repeated exposure:	May cause damage to organs (liver) through prolonged or repeated exposure (oral).
Reproductive toxicity:	Suspected of damaging fertility.

**Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)**

LD50 oral rat:	> 5000 mg/kg body weight (OECD 401 method) (OECD 420 method)
----------------	--

**Synthetic Hydrocarbon**

LD50 dermal rat:	> 2000 mg/kg body weight (OECD 402 method)
LC50 Inhalation - Rat:	> 5.2 mg/l/4h (OECD 403 method)

**Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)**

LD50 dermal rabbit:	3000 mg/kg body weight
ATE US (dermal):	3000 mg/kg body weight

**Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)**

LD50 oral rat:	> 5000 mg/kg body weight (OECD 401 method)
LD50 dermal rat:	> 2000 mg/kg body weight (OECD 402 method)

**Distillates (petroleum), hydrotreated light (64742-47-8)**

LD50 oral rat:	> 5000 mg/kg body weight (OECD 420 method)
LD50 dermal rabbit:	> 2000 mg/kg body weight (OECD 402 method)
LC50 Inhalation - Rat:	> 5.28 mg/l/4h (OECD 403 method)

**Distillates (petroleum), hydrotreated middle (64742-46-7)**

LD50 oral rat:	> 5000 mg/kg body weight (OECD 401 method)
LD50 dermal rabbit:	> 2000 mg/kg body weight (OECD 402 method)



**RADCOLUBE® RHP6083****MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation**

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b>	
Serious eye damage/irritation:	Not classified
<b>Synthetic Hydrocarbon</b>	
Serious eye damage/irritation:	Not classified
<b>Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)</b>	
Serious eye damage/irritation:	Not classified
<b>Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)</b>	
Serious eye damage/irritation:	Not classified
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
Serious eye damage/irritation:	Not classified
<b>Distillates (petroleum), hydrotreated middle (64742-46-7)</b>	
Serious eye damage/irritation:	Not classified
<b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b>	
Respiratory or skin sensitization:	Not classified
<b>Synthetic Hydrocarbon</b>	
Respiratory or skin sensitization:	Not classified
<b>Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)</b>	
Respiratory or skin sensitization:	Not classified
<b>Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)</b>	
Respiratory or skin sensitization:	Not classified
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
Respiratory or skin sensitization:	Not classified
<b>Distillates (petroleum), hydrotreated middle (64742-46-7)</b>	
Respiratory or skin sensitization:	Not classified
<b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b>	
Germ cell mutagenicity:	Not classified
<b>Synthetic Hydrocarbon</b>	
Germ cell mutagenicity:	Not classified
<b>Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)</b>	
Germ cell mutagenicity:	Not classified

**RADCOLUBE® RHP6083****MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation**

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)</b>	
Germ cell mutagenicity:	Not classified
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
Germ cell mutagenicity:	Not classified
<b>Distillates (petroleum), hydrotreated middle (64742-46-7)</b>	
Germ cell mutagenicity:	Not classified
<b>Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)</b>	
NOAEL (animal/male, F0/P):	18 – 54 mg/kg body weight (OECD 443 method)
NOAEL (animal/female, F0/P):	18 – 54 mg/kg body weight (OECD 443 method)
NOAEL (animal/male, F1):	18 – 167 mg/kg body weight (OECD 443 method)
NOAEL (animal/female, F1):	18 – 167 mg/kg body weight (OECD 443 method)
Additional data:	Reproduction NOAEL, oral, rat: 225 mg/kg bw/day (28 days, (OECD 422 method)), Parental NOAEL, oral, rat: 25 mg/kg bw/day (28 days, (OECD 422 method))
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (animal/male, F0/P):	≥ 3000 mg/kg body weight
<b>Distillates (petroleum), hydrotreated middle (64742-46-7)</b>	
NOAEL (animal/male, F0/P):	≥ 3000 mg/kg body weight
<b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b>	
LOAEL (oral, rat, 90 days):	125 mg/kg body weight male (OECD 408 method)
NOAEL (dermal, rat/rabbit, 90 days):	1000 mg/kg body weight (OECD 410 method)
<b>Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)</b>	
NOAEL (oral, rat, 90 days):	25 mg/kg body weight (OECD 422 method)
STOT-repeated exposure:	May cause damage to organs (liver) through prolonged or repeated exposure (oral).
<b>Distillates (petroleum), hydrotreated light (64742-47-8)</b>	
NOAEL (oral, rat, 90 days):	750 mg/kg body weight female)
NOAEC (inhalation, rat, vapor, 90 days):	≥ 0.024 mg/l Air (OECD 412 method)

**SECTION 12: Ecological information****12.1. Toxicity**

Ecology - general:

The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

**RADCOLUBE® RHP6083****MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation**

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

<b>Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)</b>	
LC50 - Fish [1]:	0.28 mg/l 96 Hours
EC50 - Crustacea [1]:	78 mg/l EC50 48h - Daphnia magna [mg/l]
NOEC chronic fish:	0.27 mg/l 48 Hours
<b>Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)</b>	
LC50 - Fish [1]:	100 mg/l Brachydanio rerio (zebra-fish)
EC50 - Crustacea [1]:	51 mg/l Daphnia magna (Water flea)
<b>Distillates (petroleum), hydrotreated middle (64742-46-7)</b>	
LC50 - Fish [1]:	1.2 mg/l Species: Oncorhynchus mykiss (Rainbow trout), 21 days
EC50 - Crustacea [1]:	2.9 mg/l Species: Daphnia magna (Water flea), 96 Hours

**12.2. Persistence and degradability**

No additional information available

**12.3. Bioaccumulative potential**

<b>Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)</b>	
Partition coefficient n-octanol/water (Log Kow):	6.7 at 20°C

**12.4. Mobility in soil**

<b>Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)</b>	
Mobility in soil:	5.24 QSAR

**12.5. Other adverse effects**

No additional information available

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Regional waste regulation:	Disposal must be done according to official regulations.
Waste treatment methods:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations:	Disposal must be done according to official regulations.
Additional information:	Do not re-use empty containers.

**SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA / ICAO / ADN / RID / ADG

# RADCOLUBE® RHP6083

## MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation

### Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

---

#### 14.1. UN number

Not regulated for transport

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT): Not applicable

Proper Shipping Name (TDG): Not applicable

Proper Shipping Name (IMDG): Not applicable

Proper Shipping Name (IATA): Not applicable

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT): Not applicable

##### TDG

Transport hazard class(es) (TDG): Not applicable

##### IMDG

Transport hazard class(es) (IMDG): Not applicable

##### IATA

Transport hazard class(es) (IATA): Not applicable

#### 14.4. Packing group

Packing group (DOT): Not applicable

Packing group (TDG): Not applicable

Packing group (IMDG): Not applicable

Packing group (IATA): Not applicable

#### 14.5. Environmental hazards

Other information: No supplementary information available.

#### 14.6. Special precautions for user

##### DOT

No data available

##### TDG

No data available

##### IMDG

No data available

##### IATA

No data available

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

---

**SECTION 15: Regulatory information****15.1. US Federal regulations**

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**15.2. International regulations****CANADA****Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)**

Listed on the Canadian DSL (Domestic Substances List)

**Synthetic Hydrocarbon**

Listed on the Canadian DSL (Domestic Substances List)

**Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)**

Listed on the Canadian DSL (Domestic Substances List)

**Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)**

Listed on the Canadian DSL (Domestic Substances List)

**Distillates (petroleum), hydrotreated light (64742-47-8)**

Listed on the Canadian DSL (Domestic Substances List)

**Distillates (petroleum), hydrotreated middle (64742-46-7)**

Listed on the Canadian DSL (Domestic Substances List)

**EU-Regulations**

No additional information available

**National regulations****Synthetic Hydrocarbon**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

**Napthalenesulfonic acid, dinonyl-, barium salt (2:1) (25619-56-1)**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

**RADCOLUBE® RHP6083****MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation**

## Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

**Mixture of aminic antioxidants, phenolic antioxidants (68411-46-1)**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

**Distillates (petroleum), hydrotreated light (64742-47-8)**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

**Distillates (petroleum), hydrotreated middle (64742-46-7)**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

**15.3. US State regulations**

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

**SECTION 16: Other information**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)


Revision date: 08/15/2025

Data sources: ECHA (European Chemicals Agency). Supplier's safety documents.

**Full text of hazard classes and H-statements**

H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard	2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.

**Hazard Rating**

Health	2 Moderate Hazard - Temporary or minor injury may occur
Flammability	1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

## **RADCOLUBE® RHP6083**

### **MIL-PRF-6083G Hydraulic Fluid, Petroleum Base, for Preservation and Operation**

#### **Safety Data Sheet**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

---

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular process or for any particular purpose. Such information stated is to the best of Radco's knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made to its accuracy, reliability, or completeness, purchasers, users and distributors are not relying on any promise, representation, or recommendation made by Radco, and Radco does not accept liability for any loss or damage that may occur from the use of this information. Final determination of suitability of any material is the sole responsibility of the user. All material should be used with caution to guard against unknown hazards. Although certain hazards are described herein, Radco does not guarantee that these are the only hazards that exist.