



XCELTHERM® CA Plus

Safety Data Sheet

Issue date: 4/22/2014

Revision date: 4/2/2024

Supersedes: 12/10/2018

Version: 3.0

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Trade name XCELTHERM® CA Plus

1.2. Recommended use and restrictions on use

Use of the substance/mixture: XCELTHERM® CA Plus is targeted for use in heat transfer fluid applications that require prolonged life in systems that are open to the atmosphere and subject to accelerated oxidation up to 450° F (232°C).

1.3. Supplier

Radco Industries Inc.
CAGE Code 6ZS16
700 Kingsland Drive
Batavia, Illinois 60510
United States
T (630) 232-7966
www.radcoind.com

1.4. Emergency telephone number

Emergency number: For Chemical Emergency Call CHEMTREC 24hr/day 7days/week
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-741-5970
(collect calls accepted)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Aspiration hazard Category 1 H304 May be fatal if swallowed and enters airways
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US):



Signal word (GHS US): Danger
Hazard statements (GHS US): H304 - May be fatal if swallowed and enters airways
Precautionary statements (GHS US): P301+P310 - If swallowed: Immediately call a poison center or doctor.
P331 - Do NOT induce vomiting.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
White mineral oil (petroleum)	CAS-No.: 8042-47-5	≥ 90	Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures**4.1. Description of first aid measures**

First-aid measures general:	Call a physician immediately.
First-aid measures after inhalation:	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact:	Wash skin with plenty of water.
First-aid measures after eye contact:	Rinse eyes with water as a precaution.
First-aid measures after ingestion:	Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation:	Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact:	None under normal conditions.
Symptoms/effects after eye contact:	None under normal conditions.
Symptoms/effects after ingestion:	Risk of lung edema.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures**5.1. Suitable (and unsuitable) extinguishing media**

Suitable extinguishing media:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media:	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard:	No fire hazard.
Explosion hazard:	No direct explosion hazard.

Hazardous decomposition products in case of fire: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment: Wear recommended personal protective equipment.

Emergency procedures: Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up: Take up liquid spill into absorbent material.

Other information: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed: Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling: Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures: Keep in a cool, well-ventilated place away from heat.

Storage conditions: Store locked up.

Packaging materials: Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

XCELTHERM® CA Plus	
No additional information available	
White mineral oil (petroleum) (8042-47-5)	
White mineral oil (petroleum) (8042-47-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Mineral oil, excluding metal working fluids Pure, highly and severely refined
ACGIH OEL TWA	5 mg/m ³ (inhalable)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023
ACGIH OEL TWA	5 mg/m ³ (inhalable)
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2023

8.2. Appropriate engineering controls

Appropriate engineering controls: Ensure good ventilation of the work station.
 Environmental exposure controls: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Appearance:	Liquid.
Color:	dark orange
Odor:	Almost odourless
Odor threshold:	No data available
pH:	No data available
Melting point:	Not applicable
Freezing point:	≤ -29 °C (Pour point)
Boiling point:	≥ 301 °C
Critical temperature:	542 °C
Critical pressure:	1516 kPa
Flash point:	≥ 193 °C
Relative evaporation rate (butyl acetate=1):	No data available
Flammability:	Not applicable.
Vapor pressure:	≤ 0.01 kPa at 20°C (68°F)
Relative vapor density at 20°C:	No data available
Relative density:	0.85 at 25°C (77°F) (Water = 1)
Solubility:	insoluble in water.
Partition coefficient n-octanol/water (Log Pow):	No data available
Auto-ignition temperature:	> 349 °C
Decomposition temperature:	No data available
Viscosity, kinematic:	17 mm ² /s at 40°C (104°F)
Viscosity, dynamic:	No data available
Explosion limits:	No data available
Explosive properties:	No data available
Oxidizing properties:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity**10.1. Reactivity**

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity (oral):	Not classified
Acute toxicity (dermal):	Not classified
Acute toxicity (inhalation):	Not classified
Skin corrosion/irritation:	Not classified
Carcinogenicity:	Not classified
Aspiration hazard:	May be fatal if swallowed and enters airways.
Viscosity, kinematic:	17 mm ² /s at 40°C (104°F)
Symptoms/effects after inhalation:	Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact:	None under normal conditions.
Symptoms/effects after eye contact:	None under normal conditions.
Symptoms/effects after ingestion:	Risk of lung edema.
STOT-single exposure:	Not classified
STOT-repeated exposure:	Not classified
Reproductive toxicity:	Not classified

White mineral oil (petroleum) (8042-47-5)

LD50 oral rat:	> 5000 mg/kg body weight (OECD 401 method)
LD50 dermal rabbit:	> 2000 mg/kg body weight (OECD 402 method)
LC50 Inhalation - Rat:	> 5 mg/l (OECD 403 method)

White mineral oil (petroleum) (8042-47-5)

Serious eye damage/irritation:	Not classified
--------------------------------	----------------

White mineral oil (petroleum) (8042-47-5)	
Respiratory or skin sensitization:	Not classified
White mineral oil (petroleum) (8042-47-5)	
Germ cell mutagenicity:	Not classified
White mineral oil (petroleum) (8042-47-5)	
IARC group:	Not classified
National Toxicity Program (NTP) Status:	Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

White mineral oil (petroleum) (8042-47-5)	
LC50 - Fish [1]:	> 100 mg/l (OECD 203 method)

12.2. Persistence and degradability

White mineral oil (petroleum) (8042-47-5)	
Persistence and degradability:	Not readily biodegradable in water.

12.3. Bioaccumulative potential

White mineral oil (petroleum) (8042-47-5)	
BCF - Other aquatic organisms [1]:	1216 l/kg (BCFBAF v3.01, estimated value)
Partition coefficient n-octanol/water (Log Pow):	5.18
Bioaccumulative potential:	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

12.4. Mobility in soil

White mineral oil (petroleum) (8042-47-5)	
Surface tension:	No data available
Organic Carbon Normalized Adsorption Coefficient (Log Koc):	2.64 (Calculated value: Source PCKOCWIN v2.0)
Ecology - soil:	Low potential for adsorption in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

Regional waste regulation:	Disposal must be done according to official regulations.
Waste treatment methods:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations:	Disposal must be done according to official regulations.
Additional information:	Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA / ICAO / ADN / RID / ADG

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT):	Not applicable
Proper Shipping Name (TDG):	Not applicable
Proper Shipping Name (IMDG):	Not applicable
Proper Shipping Name (IATA):	Not applicable

14.3. Transport hazard class(es)**DOT**

Transport hazard class(es) (DOT): Not applicable

TDG

Transport hazard class(es) (TDG): Not applicable

IMDG

Transport hazard class(es) (IMDG): Not applicable

IATA

Transport hazard class(es) (IATA): Not applicable

14.4. Packing group

Packing group (DOT):	Not applicable
Packing group (TDG):	Not applicable
Packing group (IMDG):	Not applicable
Packing group (IATA):	Not applicable

14.5. Environmental hazards

Other information: No supplementary information available.

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency’s Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
White mineral oil (petroleum)	8042-47-5	Present	Active	

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

White mineral oil (petroleum) (8042-47-5)
Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

White mineral oil (petroleum) (8042-47-5)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm


SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04/02/2024

Full text of H-phrases	
H304	May be fatal if swallowed and enters airways

NFPA health hazard	1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard	2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
NFPA reactivity	1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



Hazard Rating	
Health	1 Slight Hazard - Irritation or minor reversible injury possible
Flammability	2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II IIIA)
Physical	1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular process or for any particular purpose. Such information stated is to the best of Radco’s knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made to its accuracy, reliability, or completeness, purchasers, users and distributors are not relying on any promise, representation, or recommendation made by Radco, and Radco does not accept liability for any loss or damage that may occur from the use of this information. Final determination of suitability of any material is the sole responsibility of the user. All material should be used with caution to guard against unknown hazards. Although certain hazards are described herein, Radco does not guarantee that these are the only hazards that exist.