



RADCOLUBE® 6081

SAFETY DATA SHEET

MIL-PRF-6081E GRADE 1010 LUBRICATING OIL, JET ENGINE, NATO SYMBOL 0-133

1. PRODUCT AND COMPANY IDENTIFICATION

---

**Product Name:** RADCOLUBE® 6081

This product meets Military Specification MIL-PRF-6081E GRADE 1010, NATO Symbol 0-133.

Qualification Number 95B      Date of Approval: 14 July 2014

ISO 9001:2015 Certification Number: C2018-00035

**Recommended Use**

This product is recommended for applications that require MIL-PRF-6081E GRADE 1010 Lubricating Oil.

**National Stock Numbers (NSN):**

9150-00-273-2388      Quart  
9150-00-273-8807      Gallon  
9150-00-231-6676      55 Gallon Drum  
9150-00-985-7031      Bulk

**Company Identification**

Headquarters and Manufacturing Facility (CAGE Code 6ZS16)  
Radco Industries, Inc.  
700 Kingsland Drive  
Batavia, IL 60510

Customer information number:                      1-630-232-7966

**EMERGENCY TELEPHONE NUMBER**

**Advisory Office in case of poisoning: Chemtrec**

Chemtrec (North America):                      1-800-424-9300

2. HAZARDS IDENTIFICATION

---

**Classification of mixture:**

Aspiration Hazard, Category 1

**Hazard Pictogram:**



**Signal Word:**

DANGER

**Hazard Statements:**

H304:	May be fatal if swallowed and enters airways.
-------	---

**Precautionary Statements:**

P243:	Take precautionary measures against static discharge
-------	--



P301 + P315 +P331:	IF SWALLOWED: Do NOT induce vomiting. Get immediate medical advice/attention.
P305 + P351:	IF IN EYES: Rinse cautiously with water for several minutes.
P350:	Gently wash with soap and water.
P362:	Take off contaminated clothing and wash before reuse.
P405:	Store locked up.
P501:	Dispose of contents/container to an approved waste disposal plant.

**NFPA Hazard ID**

Health: 1  
Flammability: 1  
Reactivity: 0

**HMIS Hazard ID**

Health: 1  
Flammability: 1  
Reactivity: 0

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	%Content	CAS Number
Distillates (petroleum), hydrotreated light naphthenic	Trade Secret	64742-53-6
Polyalphaolefin	Trade Secret	Trade Secret
Additive Package	Trade Secret	Trade Secret

### 4. FIRST-AID MEASURES

**Eyes**

Immediately flush eyes with plenty of water for at least 15 minutes.

**Ingestion**

If swallowed, drink plenty of water, DO NOT induce vomiting. Immediately call a doctor.

**Inhalation**

Move to fresh air. If unconscious place in recovery position and seek medical advice. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. Remove from further exposure. Immediately call a doctor.

**Skin**

Wash exposed skin with soap and water.

### 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

For small fires use carbon dioxide, dry chemical or foam.  
For large fires use alcohol-type foam, universal type foam or water fog.

**Fire-Fighting Equipment**

Firefighter should wear normal protective equipment (full bunker gear) and positive-pressure contained breathing apparatus. Water can be used to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Water runoff can cause environmental damage. Dike and collect water used to fight fires.

**Special Fire-Fighting Procedures**

Use water spray to cool fire-exposed containers and structures. If a rail or tank truck is involved in a fire, isolate for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible,



withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

## 6. ACCIDENTAL RELEASE MEASURES

Wear protective clothing when taking up spill. Eliminate sources of ignition. This product is insoluble in water and will float on the surface. Prevent from entering sewers or drains. Should this product enter sewers or drains, it should be pumped out into an open vessel.

## 7. HANDLING AND STORAGE

### Handling

Do not breathe vapors/dust. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

### Storage

Do not store in open or unlabeled containers. Keep container tightly closed in a dry and well-ventilated place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

Components	Occupational exposure limits
Distillates (petroleum), hydrotreated light naphthenic	ACGIH TLV: (United States, 4/2014) TWA = 5 mg/m <sup>3</sup> 8 hours (Inhalable fraction) NIOSH PEL: (United States, 10/2013) TWA = 5 mg/m <sup>3</sup> 10 hours (Mist) NIOSH PEL: (United States, 10/2013) STEL = 10 mg/m <sup>3</sup> 15 minutes (Mist) OSHA PEL: (United States, 2/2013) TWA = 5 mg/m <sup>3</sup> 8 hours (Mist)
Polyalphaolefin	None established
Additive Package	None established

### Respiratory Protection

Use with adequate ventilation. Avoid breathing vapor. If heated and ventilation is inadequate, use NIOSH certified respirator, which will protect against organic vapor.

### Hand Protection

Wear clothing and gloves that cannot be penetrated by chemicals or oil.

### Eye Protection

Safety glasses, chemical goggles, or face shields recommended to prevent contact.

### Other Protection

Do not eat, drink, or smoke when handling this product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Straw yellow to amber liquid
Odor:	Faint petroleum odor
Odor threshold:	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Evaporation Rate (ASTM D972):	Not available
Flash point Cleveland Open Cup (ASTM D92):	159°C (319°F)
Flash point Pensky-Martens (ASTM D93):	Not determined



Flammability (solid, gas):	Non-flammable
Lower flammability limit:	Not determined
Upper flammability limit:	Not determined
Initial boiling point and boiling range:	Not determined
Melting point/freezing point:	< -60°C (-76°F)
Partition coefficient (n-octanol/water), Log P <sub>ow</sub> :	Not determined
pH:	Not applicable
Solubility:	Water insoluble
Relative density (ASTM D1298) 15.6°C/15.6°C:	0.87
Vapor density:	Not determined
Vapor pressure:	< 0.1 mmHg at 25°C (77°F)
Viscosity (ASTM D445):	11 mm <sup>2</sup> /s (cSt) at 37.8°C (100°F) 2,400 mm <sup>2</sup> /s (cSt) at -40°C (-40°F)

## 10. STABILITY AND REACTIVITY INFORMATION

### Materials to avoid

Avoid exposure to materials that are highly oxidizing.

### Hazardous polymerization

Does not occur.

### Hazardous decomposition products

Incomplete combustion may give various cracked and oxidized hydrocarbons.

### Stability

Stable

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity	Method	Species	Result
Polyalphaolefin	Dermal	Rat	LD <sub>50</sub> > 2000 mg/kg
	Inhalation	Rat	LC <sub>50</sub> = 5.0 mg/L after 1 hour
	Oral	Rat	LD <sub>50</sub> > 2000 mg/kg
Distillates (petroleum), hydrotreated light naphthenic	Dermal	Rabbit	LD <sub>50</sub> > 5000 mg/kg
	Inhalation	Rat	LC <sub>50</sub> > 5.53 mg/L after 4 hours
	Oral	Rat	LD <sub>50</sub> > 5000 mg/kg (body weight)
Additive Package	--	--	Not classified

Aspiration hazard	Test Method	Species	Result
Polyalphaolefin	OECD 403	Rat	Aspiration hazard, category 1
Distillates (petroleum), hydrotreated light naphthenic	--	--	Aspiration hazard, category 1
Additive Package	--	--	Not classified

Carcinogenicity	Results
Polyalphaolefin	Not classified as carcinogen by IARC, NTP and OSHA.
Distillates (petroleum), hydrotreated light naphthenic	Not classified as carcinogen by IARC, NTP and OSHA.
Additive Package	Not classified as carcinogens by IARC, NTP and OSHA.



Eye damage / irritation	Test Method	Species	Results
Polyalphaolefin	OECD 405	Rabbit	Not irritating
Distillates (petroleum), hydrotreated light naphthenic	OECD 405	Rabbit	Not irritating
Additive Package	--	--	Not classified

Germ cell mutagenicity	Test Method	Species	Results
Polyalphaolefin	OECD 471	<i>S. typhimurium</i>	Not mutagenic
Distillates (petroleum), hydrotreated light naphthenic	OECD 471	<i>S. typhimurium</i>	Not mutagenic
	OECD 474	Mouse	Not mutagenic
Additive Package	--	--	Not classified

Reproductive toxicity	Test Method	Species	Results
Polyalphaolefin	OECD 415	Rat	No reproductive harm
Distillates (petroleum), hydrotreated light naphthenic	OECD 421	Rat	NOAEL ≥ 1000 mg/kg/day
Additive Package			Not classified

**Respiratory sensitization**

No data available

Skin sensitization	Test Method	Species	Results
Polyalphaolefin	OECD 406	Guinea pig	Not sensitizing
Distillates (petroleum), hydrotreated light naphthenic	OECD 406	Guinea pig	Not sensitizing
Additive Package	--	--	Not classified

Skin corrosion/irritation	Test Method	Species	Results
Polyalphaolefin	OECD 404	Rabbit	Not irritating
Distillates (petroleum), hydrotreated light naphthenic	OECD 404	Rabbit	Not irritating
Additive Package	--	--	Not classified

**Specific target organ toxicity (STOT)-repeated exposure**

No data available

**Specific target organ toxicity (STOT)-single exposure**

No data available

**12. ECOLOGICAL CONSIDERATIONS**

Aquatic Toxicity	Test Method	Species	Results
Polyalphaolefin	OECD 203	<i>D. magna</i>	NOEL = 125 mg/L after 21 days
	OECD 211	<i>O. mykiss</i>	LL <sub>50</sub> > 1000g/L after 96 hours
	DIN 38412-8	<i>P. putida</i>	EC <sub>50</sub> > 10g/L after 16 hours
Distillates (petroleum), hydrotreated light naphthenic	OECD 201	<i>Alga</i>	NOEL ≥ 100 mg/L after 72 hours
	OECD 202	<i>Daphnia sp.</i>	NOEL > 10,000 mg/L after 48 hours
	OECD 203	<i>P. promelas</i>	LL <sub>50</sub> > 100 mg/L after 96 hours
	OECD 211	<i>D. magna</i>	NOEL = 10 mg/L after 21 days
	QSAR	<i>O. mykiss</i>	NOELR ≥ 1000 mg/L after 14 days
Additive Package	--	--	Not classified

Biodegradation	Test Method	Results
Polyalphaolefin	OECD 301B	Not readily biodegradable: 15% after 28 days in water
Distillates (petroleum), hydrotreated light naphthenic	OECD 301F	Inherently biodegradable: 77% after 28 days in water
Additive Package	--	No data available



Partition Coefficient n-octanol / water (Log K <sub>ow</sub> )	Results
Polyalphaolefin	Log K <sub>ow</sub> = 10.09
Distillates (petroleum), hydrotreated light naphthenic	No data available
Additive Package	No data available

### 13. DISPOSAL INFORMATION

---

This unused material, when discarded or disposed of, is not specifically listed as a hazardous waste in Federal regulations; however, it could be considered hazardous if it meets criteria for being toxic, corrosive, ignitable, or reactive according to U.S. EPA definitions (40 CFR Subpart C). This material could also become hazardous waste if it is mixed with or comes into contact with a listed hazardous waste. If it is a hazardous waste, regulations in 40 CFR 262-266, 268, 270, and 279 may apply.

### 14. TRANSPORT INFORMATION

---

#### United States Department of Transportation (DOT)

Not regulated

#### Canada Transport - Transportation of Dangerous Goods (TDG)

Not regulated

#### International Air Transport Association (IATA)

Not regulated

#### International Carriage of Dangerous Goods by Inland Waterways (AND)

Not regulated

#### International Carriage of Dangerous Goods by Rail (RID)

Not regulated

#### International Carriage of Dangerous Goods by Road (ADR)

Not regulated

#### International Civil Aviation Organization (ICAO)

Not regulated

#### International Maritime Dangerous Goods Code (IMDG Code)

Not regulated

### 15. REGULATORY INFORMATION

---

#### California (Proposition 65)

This product does not contain any of the substances known to the State of California to cause cancer, birth defects, or reproductive harm.

#### CERCLA Reportable Quantity

This product is not reportable under 40 CFR Part 302.4.

#### Environmental Protection Agency

None of the ingredients are listed

#### National Toxicology Program (NTP)

None of the ingredients are listed.



**OSHA Hazard Communication Standard**

Not hazardous per 29 CFR 1910.1200(d).

**SARA Title III Section 302 Extremely Hazardous Substances (40 CFR Part 355)**

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

**SARA Title III Sections 311/312 Hazardous Categorization (40 CFR Part 370)**

Hazardous categories for this product are: Acute = no; Chronic = no; Fire = no; Pressure = no; Reactive = no.

**SARA Title III Section 313 (40 CFR Part 372)**

This product is not regulated under Section 313 of SARA and 40 CFR Part 372.

**U.S. Inventory (TSCA)**

Listed on inventory.

**Australia Inventory (AICS)**

Listed on inventory.

**Canada Inventory (DSL)**

All of the ingredients are listed.

**China (CICS)**

None of the ingredients are listed.

**EC Inventory (EINECS/ELINCS)**

In Compliance

**International Agency for Research on Cancer (IARC)**

None of the ingredients are listed.

**Japan Inventory (MITI)**

Listed on inventory.

**Korea Inventory (ECL)**

Listed on inventory.

**16. OTHER INFORMATION**

---

Safety Data Sheet Creation Date: 14 July 2014

Safety Data Sheet Revision Date: 8 October 2018

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PARTICULAR PROCESS OR FOR ANY PARTICULAR PURPOSE. SUCH INFORMATION STATED IS TO THE BEST OF RADCO'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE TO ITS ACCURACY, RELIABILITY, OR COMPLETENESS, PURCHASERS, USERS AND DISTRIBUTORS ARE NOT RELYING ON ANY PROMISE, REPRESENTATION, OR RECOMMENDATION MADE BY RADCO, AND RADCO DOES NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL SHOULD BE USED WITH CAUTION TO GUARD AGAINST UNKNOWN HAZARDS. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, RADCO DOES NOT GUARANTEE



THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

RADCOLUBE® is a registered trademark of Radco Industries, Inc.