



# XCEL THERM® 445FP HEAT TRANSFER FLUID

## SAFETY DATA SHEET

Issue Date: 3 January 2002

Revision Date: 16 July 2018

Revision Number: 5.0

---

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product Identifier

Product Name:

XCEL THERM® 445FP Heat Transfer Fluid

ISO 9001:2015 Certification Number:  
C2018-00035

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Flash point of 229°C (445°F) that meets Coast Guard Marine requirements

#### 1.3 Details of the supplier of the safety data sheet

Headquarters and Manufacturing Facility  
Radco Industries, Inc.  
700 Kingsland Drive  
Batavia, IL 60510  
CAGE Code 6ZS16

Customer information number: 1-630-232-7966

#### 1.4 Emergency Telephone Number

Advisory Office in case of poisoning: Chemtrec  
Chemtrec (North America): 1-800-424-9300

---

### SECTION 2. HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

Not classified as a hazardous substance.

Classification of mixture is in accordance with United Nations (UN) Globally Harmonized System of Classification and Labelling of Chemicals (GHS), sixth revised edition (2015), and United States Standard 29 CFR 1910 Occupational Safety and Health Standards.

See SECTION 16 for toxicity category definitions.

#### 2.1 Label elements

##### Hazard pictograms:

None

##### Signal word:



# SAFETY DATA SHEET

## XCELTHERM® 445FP HEAT TRANSFER FLUID

Issue Date: 2 January 2002  
Revision Date: 16 July  
2018  
Revision: 5.0

None

### Hazard statements

None

### Precaution statements

P101:	If medical advice is needed, have product container or label at hand.
P202:	Do not handle until all safety precautions have been read and understood.
P270:	Do not eat, drink or smoke when using this product.
P273:	Avoid release to the environment.
P280:	Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P331 + P315:	IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Get immediate medical advice/attention.
P303 + P353:	IF ON SKIN (or hair): Rinse skin with water/shower.
P304 + P340 + P342 + P315:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms, get immediate medical advice/attention.
P305 + P351 + P338 + P310:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
P306 + P363:	IF ON CLOTHING: Wash contaminated clothing before reuse.
P404:	Store in a closed container.
P501:	Dispose of contents/container to in accordance with local/regional/national/international regulation.

## 2.2 Other hazards

### PBT and vPvB

This product is not PBT and vPvB.

### NFPA Hazard ID

Health: 1  
Flammability: 1  
Reactivity: 0

### HMIS Hazard ID

Health: 1  
Flammability: 1  
Reactivity: 0

---

## SECTION 3. Composition/information on ingredients

### 3.1 Substances



**SAFETY DATA SHEET**  
**XCELTHERM® 445FP HEAT TRANSFER FLUID**

Issue Date: 2 January 2002  
Revision Date: 16 July 2018  
Revision: 5.0

Distillates (petroleum), hydrotreated heavy paraffinic

Index number:  
CAS number:  
EC number:  
REACH number:  
Synonyms:

649-467-00-8  
64742-54-7  
265-157-1  
01-2119484627-25  
Base oil

**3.2 Mixtures**

**Description of mixture:**

Single component of distillates (petroleum), hydrotreated heavy paraffinic

Component	CAS Number	EC Number	%Content	Classification of Labeling	M-Factor
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	≥ 90%	Not classified	0

M-Factor determinations are in accordance with UN GHS, sixth revised edition (2015).

See SECTION 16 for full text of the toxicity categories and H-statements listed in this section.

**Indicative occupational exposure limit values**

Component	Specific Concentration limits
Distillates (petroleum), hydrotreated heavy paraffinic	See SECTION 8. for specific concentration limits.

**SECTION 4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

**Eye contact**

Upon accidental eye exposure, wash the eyes promptly with water for at least 20 minutes. If wearing contact lenses, remove them if safe to do so, and continue washing. Get medical attention immediately.

**Ingestion**

If swallowed, do not induce vomiting. Rinse mouth out with water. Get medical attention immediately.

**Inhalation**

If respiratory irritation, dizziness, or nausea occurs, move to fresh air and keep at rest in a comfortable position for breathing. If symptoms persist or unconsciousness occurs, seek immediate medical assistance.

**Skin contact**

Wash skin thoroughly with mild soap and plenty of water for at least 20 minutes. If irritation develops, seek medical advice.

**Note to physicians**

Treat symptomatically.

**4.2 Most important symptoms and effects, both acute and delayed**

**Acute symptoms**



# SAFETY DATA SHEET

## XCELTHERM® 445FP HEAT TRANSFER FLUID

Issue Date: 2 January 2002

Revision Date: 16 July

2018

Revision: 5.0

### Eye exposure symptoms

Direct eye exposure may lead to redness and lacrimation (crying tears).

### Ingestion symptoms

Small amounts may cause nausea. Large amounts may lead to abdominal obstruction (cramps), constipation or diarrhea.

### Inhalation symptoms

May cause irritation of the nose, throat, and lungs.

### Skin exposure symptoms

Short-term exposure is not expected to cause irritation.

### Delayed symptoms

#### Eye exposure symptoms

None expected, however seek medical attention if irritation persists.

#### Ingestion symptoms

None expected, however seek medical attention if abdominal obstruction, constipation or diarrhea persists.

#### Inhalation symptoms

None expected, however seek medical attention if respiratory irritation persists.

#### Skin exposure symptoms

Repeated exposure may lead to irritation. If rash develops, seek medical attention.

### 4.3 Indication of any immediate medical attention and special treatment needed

Suggestions for clinical testing and medical monitoring for delayed effects are not known. Use first aid when applicable, and seek guidance from a medical physician for specific treatment.

---

## SECTION 5. FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing media includes alcohol-resistant foam, carbon dioxide, dry chemical or water fog.

### 5.2 Special hazards arising from the substance or mixture

No data is available.

### 5.3 Advice for firefighters

#### Fire-Fighting Equipment

Firefighter should wear normal protective equipment (full bunker gear) and positive-pressure contained breathing apparatus. Water can be used to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Water runoff can cause environmental damage. Dike and collect water used to fight fires.

#### Special Fire-Fighting Procedures

Use water spray to cool fire-exposed containers and structures. If a rail or tank truck is involved in a fire, isolate for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures



**SAFETY DATA SHEET**  
**XCELTHERM® 445FP HEAT TRANSFER FLUID**

Issue Date: 2 January 2002  
 Revision Date: 16 July 2018  
 Revision: 5.0

**For non-emergency personnel**

Wear personal protective equipment (PPE). Eliminate sources of ignition, if safe to do so. Avoid breathing vapors or mist. Evacuate to designated safe areas.

**For emergency responders**

If possible, move individual to safe area, and treat symptomatically.

**6.2 Environmental precautions**

Contain spill, if safe to do so. Prevent from entering sewers or drains.

**6.3 Methods and material for containment and cleaning up**

Use oil absorbent material to soak up product on the ground. Should this product enter sewers or drains, it should be pumped out into an open vessel. The recovered material should be discarded as hazardous waste.

**6.4 Reference to other sections**

If appropriate, refer to SECTION 8 and SECTION 13 for additional information.

**SECTION 7. HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

Use personal protective equipment (PPE) when handling this product. Smoking, eating and drinking should be prohibited in the application area.

**7.2 Conditions for safe storage, including any incompatibilities**

Do not store in open or unlabeled containers. Keep container tightly closed in a dry and well-ventilated place.

**7.3 Specific end use(s)**

For heat transfer systems that require minimum 229°C (445°F) flash point fluid.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

Component	Occupational exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV: (United States, 4/2014) TWA = 5 mg/m <sup>3</sup> 8 hours (Inhalable fraction)
	NIOSH PEL: (United States, 10/2013) TWA = 5 mg/m <sup>3</sup> 10 hours (Mist)
	NIOSH PEL: (United States, 10/2013) STEL = 10 mg/m <sup>3</sup> 15 minutes (Mist)
	OSHA PEL: (United States, 2/2013) TWA = 5 mg/m <sup>3</sup> 8 hours (Mist)

**Biological exposure limits**

None established for any of the disclosed components.

**8.2 Exposure controls**

**Appropriate engineering controls**

Practice general industrial hygiene. Do not eat, drink or smoke near product. Wash hands after handling. Remove clothing and wash separate from other laundry.

**Personal protective equipment (PPE)**

**Eye/face protection**



# SAFETY DATA SHEET

## XCELTHERM® 445FP HEAT TRANSFER FLUID

Issue Date: 2 January 2002  
Revision Date: 16 July  
2018  
Revision: 5.0

Safety glasses, chemical safety goggles and/or face shields are recommended when handling this product.

### Skin protection

For extended handling, wear oil resistant gloves such as neoprene. Nitrile gloves may be appropriate for short handling periods use. Contact a government approved or accredited manufacturer for specific recommendations.

### Other protections

Wear protective clothing ensuring minimal skin exposure. Protective clothing should be chemically impervious to oils and other solvents.

### Respiratory protection

Use with adequate ventilation. Avoid breathing vapor. If heated and ventilation is inadequate, use NIOSH certified respirator, which will protect against organic vapor.

### Environmental exposure controls

Do not allow product to reach ground water, water course, or sewage systems. Stop leaks, if safe to do so. Contain spills with absorbent or adsorbent materials.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance:	Clear, light-yellow liquid
Odor:	Faint petroleum odor
Odor threshold:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Evaporation Rate:	<0.04 (butyl acetate = 1)
Explosive properties:	Not available
Flammability (solid, gas):	Non-flammable
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Flash point Cleveland Open Cup (ASTM D92):	229°C (445°F)
Flash point Pensky-Martens (ASTM D93):	193°C (379°F)
Initial boiling point and boiling range:	> 300°C (572°F)
Melting point/freezing point:	Not determined
Oxidizing properties:	Non-oxidizing
Partition coefficient (n-octanol/water), Log P <sub>ow</sub> :	Not available
pH:	Not applicable
Relative density (ASTM D1298) 15.6°C/15.6°C (60°F/60°F):	0.86
Solubility in water:	Insoluble
Vapor density:	Not available
Vapor pressure:	< 0.01 mmHg at 20°C (68°F)
Viscosity (ASTM D445):	29.5 cSt at 40°C (104°F) 5.3 cSt at 100°C (212°F)

### 9.2 Other information

No further information is available.

## SECTION 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Non-reactive in its original state.

### 10.2 Chemical stability

Stable in its original state.



### 10.3 Possibility of hazardous reactions

Does not occur.

### 10.4 Conditions to avoid

Oxidizing materials

### 10.5 Incompatible materials

Keep away from strong oxidizing agents.

### 10.6 Hazardous decomposition products

Decomposition of this product under fire conditions may produce carbon oxides, phenols, and other decomposition products.

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Acute toxicity	Method	Species	Result
Distillates (petroleum), hydrotreated heavy paraffinic	Dermal	Rabbit	LD <sub>50</sub> > 5000 mg/kg
	Inhalation	Rat	LC <sub>50</sub> > 5.53 mg/L after 4 hours
Distillates (petroleum), hydrotreated heavy paraffinic	Oral	Rat	LD <sub>50</sub> > 5000 mg/kg body-weight
	OECD 403	Rat	LC <sub>50</sub> > 5.53 mg/L after 4 hours

Carcinogenicity	Results
Distillates (petroleum), hydrotreated heavy paraffinic	Non-carcinogenic

Eye damage / irritation	Test Method	Species	Results
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 405	Rabbit	Not irritating

Germ cell mutagenicity	Test Method	Species	Results
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 471	<i>S. typhimurium</i>	Not mutagenic

Reproductive toxicity	Test Method	Species	Results
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 421	Rat	NOAEL ≥ 1000 mg/kg body-weight/day

Respiratory sensitization	Results
Distillates (petroleum), hydrotreated heavy paraffinic	No data available

Skin sensitization	Test Method	Species	Results
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 406	Guinea pig	Not sensitizing



**SAFETY DATA SHEET**  
**XCELTHERM® 445FP HEAT TRANSFER FLUID**

Issue Date: 2 January 2002  
 Revision Date: 16 July 2018  
 Revision: 5.0

Skin corrosion/irritation	Test Method	Species	Results
Distillates (petroleum), hydrotreated heavy paraffinic	--	Rabbit	Not irritating

Specific target organ toxicity (STOT)-repeated exposure	Test Method	Species	Results
Distillates (petroleum), hydrotreated heavy paraffinic	Dermal	Rat	NOAEL < 30 mg/kg/day
	Inhalation	Rat	NOAEL > 980 mg/m <sup>3</sup>
	Oral	Rat	NOAEL < 125 mg/kg/day

Specific target organ toxicity (STOT)-single exposure	Results
Distillates (petroleum), hydrotreated heavy paraffinic	No data available

**11.2 Other information**

See SECTION 16 for toxicity references.

**SECTION 12. ECOLOGICAL INFORMATION**

**12.1 Toxicity**

Aquatic Toxicity	Test Method	Species	Results
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 202	<i>Daphnia</i>	NOEL > 10,000 mg/L
	OECD 203	<i>sp.</i>	NOEL ≥ 100 mg/L
	(Q)SAR	<i>P. promelas</i>	NOEL ≥ 1000 mg/L
		<i>O. mykiss</i>	

Terrestrial Toxicity	Results
Distillates (petroleum), hydrotreated heavy paraffinic	No data available

**12.2 Persistence and degradability**

Biodegradation	Results
Distillates (petroleum), hydrotreated heavy paraffinic	Not readily biodegradable

**12.3**

**Bioaccumulative potential**

**Bioconcentration Factor (BCF)**

No BCF data is available

**Partition Coefficient n-octanol / water (Log K<sub>ow</sub>)**

No data is available.

**12.4 Mobility in soil**

**Soil Mobility**

No data available





**SAFETY DATA SHEET**  
**XCELTHERM® 445FP HEAT TRANSFER FLUID**

Issue Date: 2 January 2002  
Revision Date: 16 July 2018  
Revision: 5.0

**12.5 Results of PBT and vPvB assessment**

Chemical	Results
Distillates (petroleum), hydrotreated heavy paraffinic	The substance is not PBT / vPvB.

**12.6**

**Other adverse effects**

No further information is available

**SECTION 13. DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods**

This unused material, when discarded or disposed of, is not specifically listed as a hazardous waste in Federal regulations; however, it could be considered hazardous if it meets U.S. EPA (40 CFR Subpart C) criteria for being toxic, corrosive, ignitable, or reactive. This material could also become hazardous waste if it is mixed with or meets a listed hazardous waste. If it is a hazardous waste, regulations in 40 CFR 262-266, 268, 270, and 279 may apply.

**SECTION 14. TRANSPORTATION INFORMATION**

**United States Department of Transportation (DOT)**

Not regulated

**Canada Transport - Transportation of Dangerous Goods (TDG)**

Not regulated

**International Air Transport Association (IATA)**

Not regulated

**International Carriage of Dangerous Goods by Inland Waterways (AND)**

Not regulated

**International Carriage of Dangerous Goods by Rail (RID)**

Not regulated

**International Carriage of Dangerous Goods by Road (ADR)**

Not regulated

**International Civil Aviation Organization (ICAO)**

Not regulated

**International Maritime Dangerous Goods Code (IMDG Code)**

Not regulated

**SECTION 15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Australia Inventory (AICS)**

All the ingredients are listed.

**California Proposition 65**

This product does not contain any chemicals known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

**Canadian Domestic Substances List/Non-Domestic Substances List (DSL/NDSL)**

All the ingredients are listed.



# SAFETY DATA SHEET

## XCELTHERM® 445FP HEAT TRANSFER FLUID

Issue Date: 2 January 2002  
Revision Date: 16 July  
2018  
Revision: 5.0

### China Inventory of Existing Chemical Substances (IECSC)

All the ingredients are listed.

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Reportable Quantity

This product is not reportable under 40 CFR Part 302.4.

### International Agency for Research on Cancer (IARC)

None of the ingredients are listed.

### Japan Existing and New Chemical Substances (ENCS)

All the ingredients are listed.

### Korean Existing and Evaluated Chemical Substances (KECL)

All the ingredients are listed.

### Philippines Inventory of Chemicals and Chemical Substances (PICCS)

All the ingredients are listed.

### SARA Title III Section 302 Extremely Hazardous Substances (40 CFR Part 355)

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

### SARA Title III Section 313 (40 CFR Part 372)

This product is not regulated under Section 313 of SARA and 40 CFR Part 372.

### SARA Title III Sections 311/312 Hazardous Categorization (40 CFR Part 370)

Hazardous categories for this product are:

Acute =	Chronic =	Fire =	Pressure =	Reactive =
Yes	No	No	No	No

### United States Toxic Substances Control Act (TSCA)

All the ingredients are listed.

## 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been conducted.

---

## SECTION 16. OTHER INFORMATION

Safety Data Sheet Creation Date:

2 January 2002

Safety Data Sheet Revision Date:

16 July 2018

Revision Number:

5.0

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION STATED IS TO THE BEST OF RADCO'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE TO ITS ACCURACY, RELIABILITY, OR COMPLETENESS, AND RADCO DOES NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL SHOULD BE USED WITH CAUTION TO GUARD AGAINST UNKNOWN HAZARDS. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, RADCO DOES NOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

XCELTHERM® is a registered trademark of Radco Industries, Inc.



## Toxicological References

"Distillates (petroleum), hydrotreated heavy paraffinic..." *Registration Dossier - ECHA*. European Chemicals Agency, [no date]. Web. 9 May 2017.

## Definitions

ACGIH

Association Advancing Occupational and Environmental Health

EC number

European Community number

Eye Irrit. 2

See *Eye irritation, category 2 definition*.

LC<sub>50</sub>

Lethal concentration that causes 50% death in test population.

LD<sub>50</sub>

Lethal dose that causes 50% death in test population.

HMIS

Hazardous Materials Identification System

OECD 202

OECD Guideline 202: Daphnia sp. Acute Immobilisation Test

OECD 203

OECD Guideline 203: Fish, Acute Toxicity Test

OECD 403

OECD Guideline 403: Acute Inhalation Toxicity

OECD 405

OECD Guideline 405: Acute Eye Irritation/Corrosion Test

OECD 406

OECD Guideline 406: Skin Sensitization Test

OECD 421

OECD Guideline 421: Reproduction/Developmental Toxicity Screening Test

OECD 471

OECD Guideline 471: Bacterial Reverse Mutation Test

OSHA

United States Department of Labor Occupational Safety and Health Administration

NFPA

National Fire Protection Association

PEL

Permissible exposure limit

QSAR

Quantitative structure-activity relationship model

PBT

Persistence Bioaccumulation and Toxicity

TLV

Threshold limit value

TWA

Time-weighted average

vPvB

Very persistent and very bioaccumulative