

XCELTHERM® XT HEAT TRANSFER FLUID

SAFETY DATA SHEET

Issue Date: 10 December 1999

Revision Date: 8 October 2018

Revision Number: 5.0

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product Name:

XCELTHERM® XT HEAT TRANSFER FLUID

ISO 9001:2015 Certification Number: C2018-00035

1.2 Relevant identified uses of the substance or mixture and uses advised against Heating and cooling fluid between -55°C to 345°C (-70°F to 650°F). Liquid or vapor phase to 343°C (650°F).

1.3 Details of the supplier of the safety data sheet

Headquarters and Manufacturing Facility Radco Industries, Inc. 700 Kingsland Drive Batavia, IL 60510 CAGE Code 6ZS16

Customer information number: 1-630-232-7966

1.4 Emergency Telephone Number

Advisory Office in case of poisoning: Chemtrec Chemtrec (North America): 1-800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification of the substance or mixture: Skin irritation: Category 2

Classifications of mixture is in accordance with United Nations (UN) Globally Harmonized System of Classification and Labelling of Chemicals (GHS), sixth revised edition (2015), and United States Standard 29 CFR 1910 Occupational Safety and Health Standards.

See SECTION 16 for toxicity category definitions.

2.1 Label elements

	()
Hazard pictograms:	Exclamation
Signal word:	Warning
Hazard statements	

Hazard statements	
H315:	Causes skin irritation.



Radco SAFETY DATA SHEET **XCELTHERM® XT HEAT TRANSFER FLUID**

Precaution statements

P101:	If medical advice is needed, have product container or label at hand.		
P202:	Do not handle until all safety precautions have been read and understood.		
P270:	Do not eat, drink or smoke when using this product.		
P273:	Avoid release to the environment.		
P280:	Wear protective gloves/protective clothing/eye protection/face protection.		
P301 + P331 + P315:	IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Get immediate medical advice/attention.		
P303 + P353:	IF ON SKIN (or hair): Rinse skin with water/shower.		
P304 + P340 + P342 + P315:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms, get immediate medical advice/attention.		
P305 + P351 + P338 + P310:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.		
P306 + P363:	IF ON CLOTHING: Wash contaminated clothing before reuse.		
P404:	Store in a closed container.		
P501:	Dispose of contents/container to in accordance with local/regional/national/international regulation.		

2.2 Other hazards

PBT and vPvB

This product is not PBT and vPvB based on components.

NFPA Hazard ID		HMIS Hazard I	D
Health:	1	Health:	1
Flammability:	1	Flammability:	1
Reactivity:	0	Reactivity:	0

Composition/information on ingredients SECTION 3.

3.1 Substances

<u>Alkylated aromatic</u>				
Index number:	Not available			
CAS number:	Trade secret			
EC number:	Trade secret			
REACH number:	Not available			
Synonyms:				

3.2 Mixtures

Component	CAS Number	EC Number	%Content	Classification of Labeling	M-Factor
Alkylated aromatic	Trade Secret	Trade Secret	> 90%	Skin Irrit. 2A – H319	0

M-Factor determinations are in in accordance with UN GHS, sixth revised edition (2015).

See SECTION 16 for full text of the toxicity categories and H-statements listed in this section.

Indicative occupational exposure limit values None established



SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye contact

Upon accidental eye exposure, wash the eyes promptly with water for at least 20 minutes. If wearing contact lenses, remove them if safe to do so, and continue washing. Get medical attention immediately.

Ingestion

If swallowed, do not induce vomiting. Rinse mouth out with water. Get medical attention immediately.

Inhalation

If respiratory irritation, dizziness, or nausea occurs, move to fresh air and keep at rest in a comfortable position for breathing. If symptoms persist or unconsciousness occurs, seek immediate medical assistance.

Skin contact

Wash skin thoroughly with mild soap and plenty of water for at least 20 minutes. If irritation develops, seek medical advice.

Note to physicians

Treat symptomatically.

4.2 Most important symptoms and effects, both acute and delayed

Acute symptoms

Eye exposure symptoms

Direct eye exposure may lead to redness and lacrimation (crying tears).

Ingestion symptoms

Small amounts may cause nausea. Large amounts may lead to abdominal obstruction (cramps), constipation or diarrhea.

Inhalation symptoms

May cause irritation of the nose, throat, and lungs.

Skin exposure symptoms

Short-term exposure is not expected to cause irritation.

Delayed symptoms

Eye exposure symptoms

None expected, however seek medical attention if irritation persists.

Ingestion symptoms

None expected, however seek medical attention if abdominal obstruction, constipation or diarrhea persists.

Inhalation symptoms

None expected, however seek medical attention if respiratory irritation persists.

Skin exposure symptoms

Repeated exposure may lead to irritation. If rash develops, seek medical attention.

4.3 Indication of any immediate medical attention and special treatment needed

Suggestions for clinical testing and medical monitoring for delayed effects are not known. Use first aid when applicable, and seek guidance from a medical physician for specific treatment.

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media includes alcohol-resistant foam, carbon dioxide, dry chemical or water fog.

5.2 Special hazards arising from the substance or mixture

No data is available.



Radco SAFETY DATA SHEET **XCELTHERM® XT HEAT TRANSFER FLUID**

5.3 Advice for firefighters

Fire-Fighting Equipment

Firefighter should wear normal protective equipment (full bunker gear) and positive-pressure contained breathing apparatus. Water can be used to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Water runoff can cause environmental damage. Dike and collect water used to fight fires.

Special Fire-Fighting Procedures

Use water spray to cool fire-exposed containers and structures. If a rail or tank truck is involved in a fire, isolate for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear personal protective equipment (PPE). Eliminate sources of ignition, if safe to do so. Avoid breathing vapors or mist. Evacuate to designated safe areas.

For emergency responders

If possible, move individual to safe area, and treat symptomatically.

6.2 Environmental precautions

Contain spill, if safe to do so. Prevent from entering sewers or drains.

6.3 Methods and material for containment and cleaning up

Use oil absorbent material to soak up product on the ground. Should this product enter sewers or drains, it should be pumped out into an open vessel. The recovered material should be discarded as hazardous waste.

6.4 Reference to other sections

If appropriate, refer to SECTION 8 and SECTION 13 for additional information.

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use personal protective equipment (PPE) when handling this product. Smoking, eating and drinking should be prohibited in the application area.

7.2 Conditions for safe storage, including any incompatibilities

Do not store in open or unlabeled containers. Keep container tightly closed in a dry and well-ventilated place.

7.3 Specific end use(s)

Recommended for PET production, Synthetic Fiber plants and many other applications that require a high temperature heat transfer fluid.

SECTION 8.

8.1 Control parameters

Occupational exposure limits None established



SAFETY DATA SHEET XCELTHERM[®] XT HEAT TRANSFER FLUID

Biological exposure limits

None established for any of the disclosed components.

8.2 Exposure controls

Appropriate engineering controls

Practice general industrial hygiene. Do not eat, drink or smoke near product. Wash hands after handling. Remove clothing and wash separate from other laundry.

Personal protective equipment (PPE)

Eye/face protection

Safety glasses, chemical safety goggles and/or face shields are recommended when handling this product.

Skin protection

For extended handling, wear oil resistant gloves such as neoprene. Nitrile gloves may be appropriate for short handling periods use. Contact a government approved or accredited manufacturer for specific recommendations.

Other protections

Wear protective clothing ensuring minimal skin exposure. Protective clothing should be chemically impervious to oils and other solvents.

Respiratory protection

Use with adequate ventilation. Avoid breathing vapor. If heated and ventilation is inadequate, use NIOSH certified respirator, which will protect against organic vapor.

Environmental exposure controls

Do not allow product to reach ground water, water course, or sewage systems. Stop leaks, if safe to do so. Contain spills with absorbent or adsorbent materials.

SECTION 9. PHSYICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	Water white to straw yellow, clear liquid
Odor:	Mild aromatic
Odor threshold:	Not determined
Auto-ignition temperature:	428°C (803°F)
Decomposition temperature:	< 1% mass at 343°C (650°F)
Evaporation Rate:	Not determined
Explosive properties:	Not determined
Flammability (solid, gas):	Non-flammable
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Flash point Cleveland Open Cup (ASTM D92):	135°C (275°F)
Flash point Pensky-Martens (ASTM D93):	124°C (255°F)
Initial boiling point and range:	272°C (522°F), 10% fraction
Melting point/freezing point:	<-57°C (-71°F)
Oxidizing properties:	Not determined
Partition coefficient (n-octanol/water), Log Pow:	4.55
pH:	Not applicable
Relative density (ASTM D1298) 15.6°C/15.6°C (60°F/60°F):	0.95 – 1.05
Solubility in water:	Insoluble
Vapor density (air = 1):	6.5
Vapor pressure:	0.002 mmHg at 25°C (77°F)
Viscosity (ASTM D445):	2.6 mm ² /s (cSt) at 40°C (104°F)
	1.0 mm ² /s (cSt) at 100°C (212°F)



SAFETY DATA SHEET XCELTHERM® XT HEAT TRANSFER FLUID

9.2 Other information

No further information is available.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

Non-reactive in its original state.

10.2 Chemical stability

Stable in its original state.

10.3 Possibility of hazardous reactions

Does not occur.

10.4 Conditions to avoid

Oxidizing materials

10.5 Incompatible materials

Keep away from strong oxidizing or reducing agents.

10.6 Hazardous decomposition products

Decomposition of this product under fire conditions may produce carbon oxides, phenols, and other decomposition products.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Method	Species	Result
Alkylated aromatic	Dermal	Rat	LD ₅₀ > 2000 mg/kg body-weight
	Inhalation	Rat	$LC_{50} = 3 \text{ mg/L}$
	Oral	Rat	LD ₅₀ > 2000 mg/kg body-weight

Aspiration hazard	Method	Species	Result
Alkylated aromatic	Oral	Rat	LC ₅₀ = 3 mg/L

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH, IARC, NTP or OSHA.

Eye damage / irritation	Test Method	Species	Results	
Alkylated aromatic	Read across	Rabbit	Not irritating	
Germ cell mutagenicity	Test Method	Species	Results	
Alkylated aromatic	OFCD 471	S. typhimurium	Not mutagenic	

Reproductive toxicity	Test Method	Species	Results
Alkylated aromatic	Read across	Rat	Non-toxic to reproduction

Respiratory sensitization

No data available



Radco SAFETY DATA SHEET **XCELTHERM® XT HEAT TRANSFER FLUID**

Revision Date: 8 October 2018

Revision: 5.0

Skin sensitization	Test Method	Species	Results
Alkylated aromatic	OECD 406	Guinea pig	Not sensitizing

Skin corrosion/irritation	Test Method	Species	Results
Alkylated aromatic	OECD 404	Rabbit	Irritating

Specific target organ toxicity - repeated exposure (STOT-RE) No data available

Specific target organ toxicity - single exposure (STOT-SE) No data available

11.2 Other information

See SECTION 16 for toxicity references.

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic Toxicity	Test Method	Species	Results
Alkylated aromatic	Read across	Daphnia sp.	NOEC > 0.15 mg/L after 48 hours

Terrestrial Toxicity

No data available

12.2 Persistence and degradability

Biodegradation	Test Method	Results
Alkylated aromatic		Not readily biodegradable

12.3 Bioaccumulative potential

Bioconcentration Factor (BCF)	Results
Alkylated aromatic	BCF = 580

Partition Coefficient n-octanol / water (Log Kow) No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance is not PBT / vPvB.

12.6 Other adverse effects

No further information is available.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

This unused material, when discarded or disposed of, is not specifically listed as a hazardous waste in Federal regulations; however, it could be considered hazardous if it meets U.S. EPA (40 CFR Subpart C) criteria for being toxic, corrosive, ignitable, or reactive. This material could also become hazardous waste if it is mixed with or meets a listed hazardous waste. If it is a hazardous waste, regulations in 40 CFR 262-266, 268, 270, and 279 may apply.



SAFETY DATA SHEET XCELTHERM[®] XT HEAT TRANSFER FLUID

SECTION 14. TRANSPORTATION INFORMATION

United States Department of Transportation (DOT) Not regulated

Canada Transport - Transportation of Dangerous Goods (TDG) Not regulated

International Carriage of Dangerous Goods by Inland Waterways (AND) Not regulated

International Carriage of Dangerous Goods by Rail (RID) Not regulated

International Carriage of Dangerous Goods by Road (ADR) Not regulated

International Civil Aviation Organization (ICAO) Not regulated

International Maritime Dangerous Goods Code (IMDG Code) Not regulated

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Australia Inventory (AICS) All the ingredients are listed.

California Proposition 65

This product does not contain any chemicals known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Canadian Domestic Substances List/Non-Domestic Substances List (DSL/NDSL)

All the ingredients are listed.

China Inventory of Existing Chemical Substances (IECSC) All the ingredients are listed.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Reportable Quantity This product is not reportable under 40 CFR Part 302.4.

International Agency for Research on Cancer (IARC) None of the ingredients are listed.

Japan Existing and New Chemical Substances (ENCS) All the ingredients are listed.

Korean Existing and Evaluated Chemical Substances (KECL) All the ingredients are listed.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List

This product contains 27.0% Alkylated aromatic, and it is cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List.



Philippines Inventory of Chemicals and Chemical Substances (PICCS)

All the ingredients are listed.

SARA Title III Section 302 Extremely Hazardous Substances (40 CFR Part 355)

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA Title III Section 313 (40 CFR Part 372)

This product contains 27.0% Alkylated aromatic, and is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 that is listed in 40 CFR 372.

SARA Title III Sections 311/312 Hazardous Categorization (40 CFR Part 370)

Hazardous categories for this product are: Acute = No Chronic = No Fire = No Pressure = No Reactive = No

United States Toxic Substances Control Act (TSCA)

All the ingredients are listed.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been conducted.

SECTION 16.

Safety Data Sheet Creation Date:	10 December 1999
Safety Data Sheet Revision Date:	8 October 2018
Revision Number:	5.0

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PARTICULAR PROCESS OR FOR ANY PARTICULAR PURPOSE. SUCH INFORMATION STATED IS TO THE BEST OF RADCO'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE TO ITS ACCURACY, RELIABILITY, OR COMPLETENESS, PURCHASERS, USERS AND DISTRIBUTORS ARE NOT RELYING ON ANY PROMISE, REPRESENTATION, OR RECOMMENDATION MADE BY RADCO, AND RADCO DOES NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL SHOULD BE USED WITH CAUTION TO GUARD AGAINST UNKNOWN HAZARDS. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, RADCO DOES NOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

XCELTHERM[®] is a registered trademark of Radco Industries, Inc.

Definitions	
EC number	European Community number
EU	European Union
IARC	International Agency for Research on Cancer
HMIS	Hazardous Materials Identification System
LC ₅₀	Lethal concentration that causes 50% death in test population.
NOAEL	No observed adverse effect level
NTP	National Toxicology Program, United States Department of Health and Human Services
LD ₅₀	Lethal dose that causes 50% death in test population.
NFPA	National Fire Protection Association
OECD	Organisation for Economic Co-operation and Development
OECD 404	OECD Guideline 404: Acute Dermal Irritation/Corrosion
OECD 471	OECD Guideline 471: Bacterial Reverse Mutation Test
OSHA	United States Department of Labor Occupational Safety and Health Administration
PBT	Persistence Bioaccumulation and Toxicity